



MSTRADEWOOD

Malaysian

- Exterior
- Tropical hardwoods
- Tiling substrate
- Resilient flooring underlay
- Exterior joinery
- Bond Class 3 EN314-2
- EN 636-2
- Service class: 1, 2 & 3



UK +44 28 9046 0990

ROI +353 1 531 4469

sales@mstradewood.com



Malaysian

- Exterior
- Tropical hardwoods
- Tiling substrate
- Resilient flooring underlay
- Exterior joinery
- Bond Class 3 EN314-2
- EN 636-2
- Service class: 1, 2 & 3



Malaysian "Far Eastern" hardwood throughout plywood.

Excellent quality hardwood throughout plywood from the leading manufacturer's in Malaysia.

Proven for many years as a suitable substrate for tiling & resilient floor coverings and for use in exterior joinery.

For structural use in dry, humid and exterior conditions
(In exterior conditions protect as recommended by TRADA)

TECHNICAL SPECIFICATIONS

Certification: CE2+

Environmental: EUTR compliant (MYTLAS, PEFC & FSC® available by arrangement)

Grade: BB/CC

Panel Size: 2440 x 1220mm

Available in thicknesses: 3.6, 5.5, 9.0, 12.0, 18.0 & 25.0mm

Glue type: Phenolic Ext EN 314-2 class 3

Boil test: 72 hours

Service class: 1, 2 & 3 (in service class 3 preservative treatment is required to achieve satisfactory performance).

UK +44 28 9046 0990
ROI +353 1 531 4469
sales@mstradewood.com



www.mstradewood.com