



MSTRADEWOOD

Brazilian Elliottis Plywood

- Phenolic glue
- Floor & Roof Decking
- Packaging
- Hoarding & temporary works
- EN 636-2
- Bond Class 3 EN314-2
- Service class: 1 & 2



UK +44 28 9046 0990

ROI +353 1 531 4469

sales@mstradewood.com



Brazilian Elliottis Plywood

- Phenolic glue
- Floor & Roof Decking
- Packaging
- Hoarding & temporary works
- EN 636-2
- Bond Class 3 EN314-2
- Service class: 1 & 2

From leading Brazilian manufacturers based in the southern states of Santa Catarina and Parana, Elliottis Pine Plywood is well proven in the Irish market as a versatile panel often used for packaging, floor/roof decking, hoarding and shuttering. Not suitable for tiling or as a substrate for resilient floor coverings.

The panels are available either square edged or tongue and grooved two long edges. The tongue and grooved panels are available with BBA certification.

Suitable for structural use in dry, humid and exterior conditions (In exterior conditions protect as recommended by TRADA).



TECHNICAL SPECIFICATIONS

Certification: CE2+

Environmental: FSC® certified

Grade: C+/C (sanded & repaired one face, sometimes referred to as good one side or G1S)

Panel Size: 2440 x 1220mm

Glue type: Phenolic Ext EN 314-2 class 3

Boil test: 72 hours

Service class: 1 & 2

UK +44 28 9046 0990
ROI +353 1 531 4469
sales@mstradewood.com



www.mstradewood.com